

RECEIVED
CENTRAL FAX CENTER

OCT 27 2009

1734

AMENDMENTS TO THE CLAIMS

The listing below of the claims will replace all prior versions and listings of claims in the present application:

Listing of Claims:

Claim 1 (currently amended): A method of producing a molybdenum-silicide-based heating element, said method comprising the steps of:

providing powdered molybdenum aluminosilicide material $Mo(Si_{4-x}Al_x)_2$;

mixing the powdered molybdenum aluminosilicide material with SiO_2 to provide a heating element material mixture, wherein the SiO_2 is at least 98% pure, wherein the SiO_2 present in the heating element material mixture is a silicate that does not affect molybdenum silicide crystal lattice symmetry, and wherein the heating element material mixture is free of bentonite;

forming a heating element from the heating element material mixture to provide a formed heating element; and

sintering the formed heating element, wherein after sintering the formed heating element contains substantially $Mo(Si_{1-x}Al_x)_2$ and Al_2O_3 , wherein x lies in the range of 0.4 – 0.6, and the heating element includes on its surface an oxide layer consisting essentially of Al_2O_3 that does not peel from the surface of the formed heating element under thermal cycling of the formed heating element between room temperature and about 1500°C, so that heating oven contamination in the form of

1734

peeled oxide layer particles from the formed heating element within a heating oven containing the formed heating element is prevented.

Claim 2 (canceled)

Claim 3 (canceled)

Claim 4 (previously presented): A method according to Claim 1, wherein x lies in the range of 0.45 - 0.55.

Claim 5 (previously presented): A method according to Claim 1, including the step of partially substituting at least one of Re and W for molybdenum in the aluminosilicide material.

Claim 6 (previously presented): An electrical heating element produced in accordance with the method claimed in claim 1.

Claim 7 (canceled)

Claim 8 (previously presented): A heating element according to Claim 6, wherein x lies in the range of 0.45 - 0.55.

1734

Claim 9 (previously presented): A heating element according to Claim 6, wherein molybdenum in the aluminosilicide material is partially replaced with at least one of Re and W.

Claim 10 (currently amended): A method according to claim 2_1, wherein the silicate is mullite.

Claim 11 (currently amended): A method according to claim 2_1, wherein the silicate is sillimanite.